



☞ Morsetti a vite / Screw Terminal Blocks

**Dati tecnici**

**Specifications**

Tensione ingresso	Input voltage	24 Vdc ± 10%
Corrente ingresso	Input current	35mA
Tensione max contatto	Max switching voltage	400Vac
Corrente nominale	Nominal current	6A
Carico max	Max load	1600VA
Δt on	Δt on	14mSec.
Δt off	Δt off	10mSec.
Isolamento cont. bobina	Contact coil insulation	2K5Vac
Isolamento tra contatti	Insulation between contacts	2K5Vac
Vita meccanica (relè)	Mechanical life (Relays)	1x10 <sup>7</sup> cicli / cycles
Temperatura di funzionamento	Operating temperature	0...50° C
Allacciamento	Connection	Morsetti a vite / Screw terminal blocks
Sezione cavi flessibili	Fine-wired section	max 1,5 mm <sup>2</sup>
Montaggio	Mounting	a scatto su profilo / Snap-in mounting on DIN TS32 TS35

Tipo Relè Relays	Relè 3 NA + 1 NC 3 NO + 1 NC relay		Relè 2 NA + 2 NC 2 NO + 2 NC relay		Dim. LxBxH ( mm )
	Tipo Type	Codice Code	Tipo Type	Codice Code	
KAKO ROS24	EMRSI3+1	31E017295			33x82x63
KAKO ROS24			EMRSI2+2	31E017296	33x82x63
HENGSTLER H463/1	EMRSI3+1/Z	31E017297			33x82x74
HENGSTLER H463/1			EMRSI2+2/Z	31E017298	33x82x74

EMRSI.../Z Relè Locolati / Socketed Relays

