

Typenschlüssel

Gerätesteckdose: G

Norm: D DIN

I Industriestandard

Bauform: A
B
C

Polzahl: 3
4

Beschaltung: O Ohne, Y LED gelb, G LED grün, R LED rot,
D Diode, T Transdiode, L Gleichrichter, V Varistor
E Verstärker, H1 Druckdose, S Sonderbeschaltung

Verschraubung/ 7 Pg 7 (nur Bauform C) M 8 (nur Bauform C)
Anschluß: 9 Pg 9 (nur Bauform A+B) M 12 (nur Bauform A+B)
1 Pg 11 (nur Bauform A)

PE-Position: 0 Pos. 12 Uhr 9 Pos. 9 Uhr
6 Pos. 6 Uhr 3 Pos. 3 Uhr

Farbe: G graue Dose
S schwarze Dose
T transparente Dose (grundsätzlich bei Ausführung mit LED)

Spannung: 1 12 V 5 115 V
AC/DC bzw. DC je nach Beschaltung 2 24 V 6 230 V
4 48 V

Dichtung: 1 Profildichtung
2 Flachdichtung

Kabelmaterial: 1 PVC - Leitung 3 Strahlenvernetzt
2 PUR - Leitung 4 Sonderleitung

Leitungslängen: 1 1m 5 5m
3 3m 0 10m

Bauhöhe: H hohe Bauform

Befestigung: R Rändelschraube

Sonder- S mit Hutmutter, IP 68, K Klemmkäfig mit
Verschraubung: Farbe schwarz Druckschraube
G dito, jedoch in grau W standard Pg-Farbe wechseln



Certificate of Compliance

Certificate Number: LR 103793-2

SUBMITTOR

Revision: LR 103793-2

Date Issued: June 5, 1998

Issued to: **PETERS INDU-PRODUKT GMBH**
Mercatorstrasse 41
46485 Wesel
Germany

The products listed below are eligible to bear the CSA Mark

NOTE: The "NRTL/C" indicator may appear adjacent to the CSA Mark.

Issued by: J- P, Boivin, Eng.
Montréal, QC Canada

Signature: _____

FOR


PRODUCTS

CLASS 5852 01 - SPECIAL USE ATTACHMENT PLUGS, RECEPTACLES AND CONNECTORS.
CLASS 5852 81 - ATTACHMENT PLUGS AND RECEPTACLES - CERTIFIED TO U.S. STANDARDS

Solenoid female connectors, permanent connected, types A, B, C and connector similar to A but with a neck of 22,7 mm instead of 18.5 mm. Colors black, grey and clear.

CONNECTOR A: 3 current carrying poles, + 1 ground pole, 10 Amps, 250V ac/dc max
CONNECTOR B: 2 current carrying poles, + 1 ground pole, 10 Amps, 250V ac/dc max
CONNECTOR C: 2 current carrying poles, + 1 ground pole, 6 Amps, 250V ac/dc max

Note: Certified as component for use in other Certified equipment where the suitability of the combination is determined by the Canadian Standards Association.

APPLICABLE STANDARDS

CAN/CSA-C22.2 No. 182.3-M - Special Use Attachment Plugs, Receptables and Connectors
ANSI/UL Std No. 498 (Thirteen Edition) - Attachment Plug and Receptacles

The "NRTL/C" indicator adjacent to the CSA Mark signifies that the product has been evaluated to the applicable ANSI/UL and CSA Standards, for use in the U.S. and Canada. NRTL, i.e. Nationally Recognized Testing Laboratory, is a designation granted by the U.S. Occupational Safety and Health Administration (OSHA) to laboratories which have been recognized to perform certification to U.S. Standards.